

9-pin, serial dot

TM-U950/U925



Outstanding Performance & Versatility

Prints everything from slips and receipts to journals. Ultra-fast output of up to 88 columns on A4-size paper with bi-directional, logic-seeking printing.

Reliability & Convenience

The reliability is there. Plus a wide range of handy features including automatic paper cutting and easy paper loading and ribbon changing.

Versatile Printer For Large POS Systems

Print method	9-pin, serial impact dot matrix
Print font	Font 7 x 9 / 9 x 9 Column capacity (columns)..... Receipt (Journal): 40 / 30, Slip: 88 / 66 (TM-U950) Receipt: 40 / 30, Slip: 88 / 66 (TM-U925) Character size (mm)..... 1.3 (W) x 3.1 (H) / 1.6 (W) x 3.1 (H) Character set 95 Alphanumeric, 32 International, 128 x 8 Graphic Characters per inch 16.7 cpi / 12.5 cpi
Interfaces	RS-232, Bi-directional parallel (TM-U950) RS-232 (TM-U925)
Data buffer	2 KB or 32 bytes
Print speed	311 / 233 cps
Paper	Dimensions (mm)..... Receipt (Journal): Roll paper: 69.5 ± 0.5 (W) x dia. 83.0 Slip: 70 (W) x 70 (L) to 210 (W) x 297 (L) (TM-U950) Receipt: Roll paper: 69.5 ± 0.5 (W) x dia. 83.0 Slip: 70 (W) x 70 (L) to 210 (W) x 297 (L) (TM-U925) Thickness (mm) Receipt (Journal): 0.06 to 0.09, Slip: 0.09 to 0.36 (TM-U950) Receipt: 0.06 to 0.09, Slip: 0.09 to 0.36 (TM-U925)
Copy capability	One original and four copies (for slip)
Inked ribbon	ERC-31 (Purple, Black)
Ribbon life	Purple: 7 x 10 ⁶ characters, Black: 4.5 x 10 ⁶ characters
Power	24 VDC ± 10%
Power consumption	Approx. 1.8 A (mean)
D.K.D.function	2 drivers
Reliability	MTBF: 18 x 10 ⁴ hours MCBF: 18 x 10 ⁶ lines
Overall dimensions (mm)	251 (W) x 298 (D) x 194.5 (H) (TM-U950), 251 (W) x 298 (D) x 193.7 (H) (TM-U925)
Mass (Approx.)	5.6 kg
EMC standards	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Power supply	PS-170 (option)
Factory options	MICR device
Safety standards	UL / CSA / TÜV (EN60950)

