

Optimal receipt-printing solution with unprecedented speed and print quality



Epson's constant innovations in retail printing solutions give you the best performing printers to suit your business requirements and budget.

- Produces highly effective marketing tools
 Epson's first POS thermal printer to incorporate high-quality graphics, images and logos
- Saves cost for your business in power consumption
 First thermal receipt printer in the world to be awarded the ENERGY STAR® for its outstanding power-saving feature
- Ensures high productivity even in the most demanding retail environments

Class-leading print speed of 300mm per second that minimises waiting time

Reduces paper wastage
 Adjustable top and bottom margins for optimal printing





Epson TM-T88V

TM-T88V-181 (Thai/Viet, USB+Serial, ECW)

TM-T88V-191 (Thai/Viet, USB+Serial, EDG)

SPECIFICATIONS

OPTIONS

WH-10-040: WALL C32C845040 HANGING BRACKET T88V

POWER SUPPLY COVER T88V W/O PS-180 ECW

POWER SUPPLY COVER C32C814596 T88V W/O PS-180 FDG

BUZZER FEATURE

In a hectic, fast-paced environment, boost productivity and further reduce bottlenecks with an optional buzzer that signals with a new receipt.

PRODUCT CODE

DOT DENSITY PRINT DIRECTION PAPER WIDTH

PRINTING WIDTH

PRINT FONTS

CHARACTERS PER LINE (DEFAULT) CHARACTER SPACING (DEFAULT)

LINE SPACING

CHARACTER SET

CHARACTER STRUCTURE

PRINTER SPEED NORMAL

PAGE MODE PRINTING GRAPHICS PRINTING IN MONOCHROME GRAPHICS PRINTING IN MULTI-TONE

LADDER BAR CODE, 2 DIMENSIONAL PRINTING

PAPER FEED SPEED

PAPER ROLL PAPER

THICKNESS RELIABILITY

DIMENSIONS

CASE COLOUR

Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective

EPSON is the registered trademark of Seiko

EPSON disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

	C31CA85197	TM-T88V-197 (Thai/Viet, USB+Parallel, EDG)
	C31CA85198	TM-T88V-198 (Thai/Viet, USB+Parallel, ECW)
	C31CA85202	TM-T88V-202 (SimCL, USB+Serial, ECW)
	C31CA85212	TM-T88V-212 (SimCL, USB+Serial, EDG)
	C31CA85841	TM-T88V-841 (SimCL, USB+Parallel, ECW)
	C31CA85851	TM-T88V-851 (SimCL, USB+Parallel, EDG)
	C31CA85183	TM-T88V-183 (Thai/Viet, USB+Ethernet, EDG)
	C31CA85185	TM-T88V-185 (Thai/Viet, USB+Ethernet, Buzzer, EDG)
PRINTER TYPE		
PRINTER TYPE PRINTING METHOD	Thermal Line Printing	
PRINTING METERNI	i nermai i ine Printing	

C31CA85191

180 dpi x 180 dpi [dpi: dots per inch (25.4 mm)]

Unidirectional with friction feed

80 mm (3.15")

72 mm (2.83"), 512 dot positions

42/56

0.28 mm (0.01") (2 dots)

Note: programmable by control demand

4.23 mm (0.17")

Note: programmable by control demand

95 Alphanumerical, 18 sets of International Characters, 128 x 43 pages of Extended Graphic, South Asia models carry

Thai (128 x 3) & Vietnamese (128 x 2) characters, Simplified Chinese (GB18030-2000:28,553)

12 x 24 / 9 x 17 / 9 x 24 (including 2-dot spacing horizontally)

300 mm/s (11.81"/s) 300 mm/s (11.81"/s)

300 mm/s (11.81"/s)

150 mm/s (5.91"/s) for NV/download graphics, 70mm/s (2.76"/s) for

raster graphics 100 mm/s (3.94"/s)

200 mm/s (7.87"/s) (when using Feed button)

Width: 79.5 ± 0.5 mm (3.13" ± 0.02") Diameter: 83 mm (3.27") maximum 0.06 to 0.07 mm (0.002" to 0.003")

Dark Grey / Clear White

MTBF 360,000 hours MCBF 70 million lines Auto cutter 2 million cuts

145 (W) × 195 (D) × 148 (H) mm 5.71" (W) x 7.68" (D) x 5.83" (H)

WEIGHT Approx. 1.6 kg (3.53 lbs)

AUTOCUTTER

ROLL PAPER DEVICE Built-in **POWER** 24VDC ± 7%

POWER CONSUMPTION Approx. 1.8 A (Mean)

POWER SUPPLY PS-180 (included)

PRINTER DRIVER Windows® Printer Driver (APD), OPOS, Java POS, CUPS, MAC