





24 wire, 600 cps

Super Quick Universal Banking Printer



Applications:

- Passbooks
- Cheques and Drafts
- Invoices
- Cards
- Certificates & Vouchers
- Identity Cards
- Tickets
- Labels & Barcodes

Features:

- Thicker Passbooks Handling
 - Up to 2.2 mm
- Unbeatable Print Head Life
 - 400 Million Characters
- High Reliability (MTBF)
 - 10,000 Power on Hours
 - Automatic Document
 Alignment & Edge Sensing
- Dual Interface with

 Auto Interface Switching
- Indelible Ink Ribbon
 4 Million Characters

Speed 40 Product Specifications

| Printing Technology | 24 Wire Serial Dot Matrix Printer | | Resident Fonts | Draft, Courier, Gothic, Prestige, Presentor, Script, OCR-A, OCR-B, Bold Face | |
|---|---|-----|-----------------------------|---|--|
| Printing Speed Character pitch (cpi) | 600 cps max. 15 12 10 | | | | |
| Draft | 600 480 | 400 | Resident Emulations | IBM" Personal Printer 2390+. | |
| Letter Quality | 200 164 | 133 | | Proprinter XL 24E, Proprinter | |
| Line Length | 94 columns @ 10 cpi | | | XL 24E-AGM & Epson" LQ2550 / LQ1170, IBM" 4722, Olivetti" PR40 Plus/PR2/PR2845, IBM 9068 | |
| Paper Handling | Single Sheet, Passbook (Vertical/Horizontal), Envelopes, Labels Up to 2.2 mm Width: 65 - 244 mm | | | | |
| | | | Interface Standard | Parallel IEEE 1284 bidirectional | |
| Passbook Thickness | | | monace Standard | and Serial RS232C (Automatic | |
| Single Sheet | | | S- | Interface Switching) | |
| Come Comphility | Length: 70 - 470 mm | | Buffer Memory | 64 KB (selectable) | |
| Copy Capability | 1+5 (0.65 mm) | | Reliability (MTBF) | 10,000 Power On Hours | |
| Special Functions | Automatic Gap Adjustment (AGA), Auto Alignment, Auto Border Recognition, Optical Mark Reading, Automatic Set-up (automatic recognition of marked values) | | Print Head Life | 400 Million Characters | |
| | | | Ribbon Life | 4 Million Characters, High Density Indelible Ink | |
| | | | Noise Level | < 55 dBA | |
| Graphic Resolution (DPI) | 60, 120, 180, 240, 360 (horizontal) 72, 90, 180, 216, 360 (vertical) | | Power Supply | Universal - 100 to 230V Frequency - 50Hz / 60Hz | |
| Vertical Spacing | 6-8-12 lines/inch - 3-4-6-8-12 lines/30mm - n/60, n/72, n/180 n/216, n/360 per inch | | Power Consumption | 120W max (printing), 7W (standby) | |
| | | | Physical Dimensions (WxHxD) | 400 x 200 x 295 | |
| Horizontal Spacing | 5, 6, 7.5, 8.5, 10, 12, 15, 17.1, 20, 24 cpi and proportional | | Weight | < 12 kgs | |
| Barcodes | UPC/A UPC/E, EAN8, EAN13, Code 39, Code 128, PostNet, Codabar, ADD-ON 2, ADD-ON 5, Code 11, Code 93, BCD, MSI, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial | | Ordering Information | | |
| | | | Product Code | 3006010001 | |
| | | | Description | Dot Matrix Printer TVS SPEED 40 | |
| | | | Consumables 1036020001 | TVS SPEED 40 Ribbon Cassette | |

1 kg = 2.2lbs; 1 inch = 2.54 cms





Note: All specifications are at standard operating conditions and are subject to change without notice. All other products or brand names are registered trademarks of their respective holders.

TVS Electronics Limited 34, Developed Plots, South Phase Industrial Estate, Guindy, Chennai 600 032. India. Ph: (44) 22325506/09/42005200.

Fax: (44) 22327577

Visit us at www.tvs-e.in

| Contact | | | | | |
|---------|--|--|--|--|--|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |